



## MICRO

recessed


**EN** Round recessed spotlight in aluminium; surface lacquered; high quality lens system; precise radiation characteristic; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

**DE** Runder Einbaustrahler aus Aluminium; Oberfläche lackiert; hochwertige Linsensystem; präzise Abstrahlcharakteristik; energieeffiziente LEDs mit sehr guter Farbwiedergabe; durchkontaktiertes elektrisches Stecksystem für werkzeuglose Montage; Konverter steckerfertig vorkonfektioniert; Konverter ist separat zu bestellen

### Quickinfo

3000 K, 4000 K  
CRI  $\geq$  95 (R9  $\geq$  90)  
L90 @ 50 000 h  
up to 49 lm per spot  
non DIM, DALI-2

### Type



### Colours



### Light distributions




CRI  $\geq$  95  
R9  $\geq$  90

## Order options

COLOUR TEMPERATURE	
3000K	0
4000K	1

MATERIAL COLOUR	
● white aluminium RAL 9006	6
● black RAL 9021	8

BEAM ANGLE	
spot 16°	S
medium 24°	M
flood 33°	F



## MICRO 10 recessed



INS. POWER	COLOUR TEMP.	LUM. FLUX	ORDER CODE
0.8 W	3000 K	43lm	0 1 1 - 8 1 0 0 :: 1 ▣ ▲
	4000 K	49lm	

## Electrical accessories

**POWER SUPPLY 24V** 220-240 V AC, 200mA, 50-60 Hz,  PC II  
incl. power cable 2m + connection cable with plug 1m

TYPE	L-W-H (mm)	ORDER CODE
20 W   non DIM	111-52-22	0 1 1 - 9 2 1 1 2 1 0
15 W   DALI-2	145-33-21	0 1 1 - 9 2 1 1 1 3 0

**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for CRI≥95, colour black